

Viscosifier CX TROL

SINOMUD **Viscosifiers CX TROL** will not fish-eye and has been designed to disperse rapidly into any make-up water, even when only basic mixing equipment is available. Viscosifiers CX TROL can be used with SINOMUD Bentonite CX GEL, SINOMUD Drilling Polymer CHP and SINOMUD Drilling Polymer SUPER POLY to give a complete core recovery fluid that is solids free.

Function of SINOMUD Viscosifiers CX TROL

- Disperse readily in water, even with low shear
- Effective in fresh, salt and brackish water-based drilling fluids
- Efficiently improve filtration control, effective at low concentrations
- Encapsulate shale particles to inhibit swelling and dispersion
- Function over a wide range of salinity, hardness and PH levels
- Compatible with other drilling fluids additives, environmental
- Dosage: 0.5 to 3.0 kg/m³
- Package: 15 kg/drum

Advantages of SINOMUD Viscosifiers CX TROL

- Effective in fresh water, salt water, and brine-based fluids
- Controls fluid loss
- Inhibits hydratable, swelling shale
- Environmentally compatible
- Does not require a bactericide
- Easily mixed into low shear environment

Technical Data:

Appearance: White, free-flowing powder
PH: 6.5-8.0

Similar Products:

BARIOD	AMC	CETCO
QUICK-TROL	AUS TROL EZEE TROL	REL-PAC

Recommended Treatment:

Add CX TROL in concentration of 1.4 to 5.7 kg/m³ (0.5 to 2.0 lb/bbl) to any active system.

Mix slowly through a jet mixer or sift slowly into the vortex of a high-speed stirrer.

Recommended Industries:

- Foundation Drilling/Micro Piling
- Water Well Drilling
- Horizontal Directional Drilling